



Workstation Monitor

Complete clarity and versatility

IndigoVision's 24" Workstation Monitor is designed for pixel-perfect clarity and purpose-built for workspace versatility with full tilt, height, angle, and even complete rotation for portrait setup. Stunning visuals guaranteed and perfected to work with IndigoVision's Mini Client, Pro Client, Platinum Client, and Hybrid NVR Workstations.

Key Features & Benefits

Purposefully designed for comfort and convenience.

Enjoy full adjustability to pivot, tilt, height adjustment and swivel to suit your needs.

Excellent picture quality and consistent color representation.

Maximise your security potential with IndigoVision's Mini Client, Pro Client, Platinum Client, and Hybrid NVR Workstations.

Product Code

Workstation Monitor

110391

Specifications

General Specification	
Panel Type	In-Plane Switching Technology
Energy Class	Class A+
Built-in Devices	USB 3.0 hub
Aspect Ratio	Widescreen - 16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 60 Hz
Pixel Pitch	0.2745 mm x 0.2745 mm
Brightness	250 cd/m ²
Contrast Ratio	1000:1 (typical)
Colour Support	16.7 million colours
Response Time	5 ms typical (Fast) (gray to gray) 8 ms (Normal mode) (gray to gray)
Horizontal Viewing Angle	178°
Vertical Viewing Angle	178°
Screen Coating	Anti-glare, 3H Hard Coating
Backlight Technology	White LED edgelight system
Features	Ultra wide viewing angle, Premium Panel Guarantee, Dell Easy Arrange, Dell ComfortView
Dimensions (with stand)	Height 496.11 mm (19.53 inches) Width 537.80 mm (21.17 inches) Depth 179.57 mm (7.07 inches)
Weight (panel only)	3.39 kg (7.47 lb)
Weight (monitor and cables with stand)	5.57 kg (12.28 lb)
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Connectivity	1 x HDMI 1.4 (HDCP 1.4) 1 x DisplayPort 1.2 (HDCP 1.4) 1 x VGA 1 x SuperSpeed USB 5Gbps (USB3.2 Gen1) upstream 4 x SuperSpeed USB 5Gbps (USB3.2 Gen1)
Cables Included	<ul style="list-style-type: none"> • Power cable • DisplayPort to DisplayPort cable (1.8m) • SuperSpeed USB 5Gbps (USB3.2 Gen1) upstream cable
Electrical	100 VAC to 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 1.5 A (typical)
Compliant Standards	ENERGY STAR® certified monitor, EPEAT® Gold registered where applicable , RoHS-compliant, TCO Edge Certified Displays, BFR/ PVC free monitor (excluding external cables), Meets NFPA 99 leakage current requirements, Arsenic-free glass and Mercury-free for the panel only.
ENERGY STAR Certified	Yes

ID: WRK-MNTR 21.0 JUN 21